

Order number: 02 238 06 99

SCHELL WC flush valve SCHELLOMAT

with lever

flow rate: 1,0 - 1,3 l/s, cartridge with piston out of brass

Scope of delivery:

- lever
- flush rate regulation
- automatic jet cleaning needle
- flush valve unit with anti-vacuum device according to DIN EN 12541

Field of application / Technical data:

- shallow and deep pans
- flow pressure: from 1,2 bar
- flush volume: 6 l
- flush pipe connection: Ø 28 x 26 mm

Details:

- Material:

all parts in contact with water out of brass conform German drinking water regulation

- Surface: chrome
- Weight: 0.63 kg/pc.
- Packaging unit: 1
- Dimension: DN 20 G 3/4 ext. thread

Versions:

Dimension: DN 20 G 3/4 ext. thread

Order No.: [02 202 06 99](#)

Flow rate: 1.0 - 1.3 l/s, PA-IX 18853/II, DIN-DVGW certified, Belgaqua, chrome, PU 1, W: 0.6 kg/pc.

Dimension: DN 15 G 1/2 ext. thread

Order No.: [02 216 06 99](#)

flow rate: 0,7 - 1,0 l/s, chrome, PU 1, W: 0.63 kg/pc.

Recommended associated item:

WC pipe connection kit

Order No.: [03 209 06 99](#) or

WC flush pipe

Order No.: [03 100 06 99](#)
